

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problems Mailbox.**

(12) UK Patent Application (19) GB (11)

2 188 532 (13) A

(43) Application published 7 Oct 1987

(21) Application No 8707606

(22) Date of filing 31 Mar 1987

(30) Priority data

(31) 81/073787 (32) 31 Mar 1986 (33) JP
61/204427 20 Dec 1986

(71) Applicant
Uni-Charm Corporation

(Incorporated in Japan)

182 Shimobun, Kinsei-cho, Kawanoe-shi, Ehime-ken,
Japan

(72) Inventors
Takamitsu Igase
Hideaki Kikacka
Hiroyuki Tanji

(74) Agent and/or Address for Service
W. P. Thompson & Co., 12 Coopers Building, Church Street,
Liverpool L1 3AB

(51) INT CL⁴
A41B 13/02

(52) Domestic classification (Edition I)
A3V 1838

(56) Documents cited
GB A 2181336 GB A 2168253 GB A 2161059

(58) Field of search
A3V
Selected US specifications from IPC sub-class A41B

(54) Disposable diaper

(57) A disposable diaper comprises a water-permeable topsheet (11), a water impermeable backsheet (12), a semi-rigid absorbent body (13) interposed between said topsheet and backsheet, with water-impermeable flexible side flaps (14) extending laterally outwardly from opposite sides of the absorbent body. At least one elastic band (22) extends longitudinally of each of the side flaps to form resilient gathers along each side flap and fasteners (27) are disposed on opposite sides of one end of the diaper. Each side flap (14) comprises a first side flap (16) and a second side flap (17), said first side flap extends laterally outwardly from the absorbent body and the second side flap extends from the first side flap in a laterally divergent manner and at least one of the elastic bands (22) is associated with each of the second side flaps (17) and acts thereon to cause at least an edge portion thereof to be held, over at least a central portion of its length, in a substantially upstanding position relative to the first side flap from which it extends.

FIG.2





FIG.6



GB 2 188 532 A

FIG. 1 is a perspective view of a diaper 10. The diaper 10 has a waistband 36 with elastic 27. A front opening 11 is provided, with a flap 12 and a closure 17. A pocket 33 is visible on the side.

[illegible]

FIG.3




FIG.4




FIG.5




FIG. 6




FIG.7





FIG.8



5/7

2188532

FIG.9





FIG.10



6/7

FIG.11




FIG.12




FIG.13




FIG.14




FIG. 15




FIG. 16




FIG. 17





FIG. 18



SPECIFICATION

Disposable diaper

5 The present invention relates to a disposable diaper adapted to absorb and retain human excretions and more particularly to such disposable diapers to be worn by babies, sick persons, aged people and persons suffering incontinence, in which a selected
10 portion of each flexible side flap incorporated with elastic band is turned upwards under an elastic effect of said elastic band.

Some of the absorptive articles such as disposable
15 diapers have already adopted the side flaps constructed to be raised so that a fitness of said side flaps around the thighs of the wearer is improved and thereby leakage of excretions which would otherwise occur across the thighs can be effectively avoided, for example, as disclosed in U.S. Patent No. 4,579,556. In
20 accordance with the technique as disclosed by this U.S. Patent, along the outer edges of the rectangular absorbent body (layer) interposed between or sandwiched by the topsheet and the backsheets, the side flaps rise under elastic effect of the elastic bands
25 which are incorporated into the respective side flaps along the outer edges thereof. Such rising or turning up of the side flaps is believed to occur due to a fact that a rigidity of the absorbent body is higher than that of the side flaps and, in consequence, the elastic effect
30 of the elastic bands transmitted to said side flaps is blocked by the outer edges of said absorbent body and converted into an effect serving to turn said side flaps up.

According to this concept, however, the absorbent
35 body is restricted to a configuration having the substantially linear outer edges, i.e. the rectangular form in general and its width is also restricted, so that it is difficult for the absorbent body to be configured in any other shape suitable to improve a fitness of the
40 diaper around the wearer's body, for example, in the form of a sandglass. In addition, although the side flaps are certainly turned up as has been described above, such rising or turning up is merely bending of the side flaps along the outer edges of the absorbent
45 body. Accordingly, said side flaps might be subjected to a stress-strain due to the rigidity of said absorbent body and thereby their free flexibility might tend to be hindered, unless the height (width) of said flaps is dimensioned to be relatively large and distances
50 between the elastic gathers formed by the associated elastic bands mounted on the free ends of the respective side flaps and the associated outer edges of said absorbent body are also dimensioned to be relatively large. At the same time, said absorbent body
55 tends to be subjected to a stress-strain due to the elastic effect of said elastic bands and thereby to be irregularly deformed, resulting in various inconveniences such as deteriorated appearance of the diaper as being worn, discomfort for the wearer and poor
60 fitness of the diaper on the wearer's body, particularly a poor sealing effect around the thighs.

A typical technique to overcome the problems encountered when the side flaps including the elastic

gathers formed by the elastic bands are associated
65 with combining with a semi-rigid absorbent body is disclosed in the U.S. Patent No. 3,860,003. The technique disclosed in this U.S. Patent teaches that, when the side flaps are incorporated with the elastic
70 bands along the outer sides thereof sufficiently spaced from the associated outer edges of the absorbent body, an effective seal is obtained around the thighs without significantly hindered contractibility and flexibility of the side flaps by said elastic bands due to the rigidity of said absorbent body.

However, when the elastic bands are to be disposed
75 along the outer sides of the side flaps sufficiently spaced from the associated outer edges of the absorbent body, it will be necessary that the width of the absorbent body is dimensioned to be relatively narrow at least in the crotch area. This will result in
80 that a capacity or a volume to absorb and retain excretions is reduced in the most important area for this purpose and thereby leakage of excretions occurs around the thighs. Although the U.S. Patent No.
85 3,860,003 intends to eliminate the drawback of the prior art that the front portion of the diaper is encouraged to blossom or pouch outwards as though it were trying to form a damp apron, this intention will not be achieved when the respective elastic bands are
90 sufficiently spaced from the associated outer edges of the absorbent body.

Thus, the prior art anticipates no measure to overcome the above-mentioned problems which are effectively solved, according to the present invention,
95 by a particular arrangement of the side flaps as will be described in detail later.

A principal object of the present invention is, for the purpose of effectively overcoming the inconveniences as set forth above, to provide a disposable diaper so
100 improved to achieve an effective seal around the thighs as can not be expected from the prior art and thereby to minimize a possible leakage of excretions around the thighs.

Other objects and advantages of the present invention will be apparent from reading the following
105 description.

According to the present invention there is provided a disposable diaper comprising a water-permeable
110 topsheet, a water-impermeable backsheets, a semi-rigid absorbent body interposed between said topsheet and backsheets, water-impermeable flexible side flaps extending laterally outwardly from opposite sides of said absorbent body, at least one elastic band extending longitudinally of each of said side flaps and adapted to form resilient gathers along each of said
115 side flaps and fasteners disposed on opposite sides of one end of said diaper, characterised in that each of said side flaps comprises a first side flap and a second side flap, said first side flap extending laterally outwardly from said absorbent body and said second side flap extending from said first side flap in a laterally divergent manner and in that at least one of said elastic bands is associated with each of said
120 second side flaps and acts thereon to cause at least an edge portion thereof to be held over at least a central portion of the length thereof in a substantially

upstanding position relative to the first side flap from which it extends.

The present invention resides in a disposable diaper including a water-permeable topsheet, a water-im-
 5 permeable backsheet, an absorbent body interposed between said both sheets and having semi-rigid, water-impermeable side flaps disposed on laterally
 10 opposite sides of said absorbent body and having a high flexibility, elastic bands adapted to form elastic gathers extending longitudinally of said side flaps and
 15 tape fasteners disposed on laterally opposite sides in a rear side area of the diaper, wherein each of said side flaps includes a first flap disposed outside said
 20 absorbent body and a second flap diverged from said side flap, having the associated one of said elastic bands incorporated therein and turned up under an
 25 elastic effect of said associated elastic band at least along a line of the divergence.

With such arrangement of the present invention, said second flap is turned up from said line of
 20 divergence transversely of said first flap so that the gather portion of said second flap functions to achieve a desired effect independently of the rigidity of said
 25 absorbent body even if a distance from the outer edge of said absorbent body to said elastic band is relatively small.

The invention will be further illustrated by reference to the accompanying drawings, in which:

Fig. 1 is a perspective view showing a diaper
 30 constructed in accordance with the present invention as completely assembled;

Fig. 2 is a developed perspective view showing a top side of said diaper;

Fig. 3 is a sectional view taken along a line 3-3 in Fig.
 35 2;

Fig. 4 is a sectional view taken along a line 4-4 in Fig.
 2;

Fig. 5 is a sectional view taken along a line 5-5 in Fig.
 2;

Fig. 6 is a partial perspective view showing a side
 40 portion of said diaper;

Fig. 7 is a plan view showing said diaper as in the process of its formation;

Fig. 8 is a plan view showing said diaper as having
 45 been completed after said process of formation;

Fig. 9 is a developed plan view showing said diaper as having been longitudinally extended;

Figs. 10 to 17 are partial perspective views showing
 50 other embodiments within the present invention of said side portion; and

Fig. 18 is an enlarged schematic sectional view
 taken along a line 18-18 in Fig. 9.

Referring to Figs. 1 to 6, a diaper of the invention comprises a water-permeable topsheet 11, a water-
 55 impermeable backsheet 12, a semi-rigid absorbent body 13 and side flaps 14. Each of said side flaps 14 consists of a first flap 16 and a second flap 17. The first flap 16 consists, in turn, of respective portions of the
 60 topsheet 11 and the backsheet 12 as well as a portion of the second flap 17 which extend outwards from each side edge of the absorbent body 13. The width of said extending portions of the topsheet 11 may be smaller than that of the backsheet 12. The second flap 17 lies upon the top surface of the first flap 16 and
 65 outside portions of these two flaps lying one upon

another are so joined to each other as to define a

pocket 18 therebetween. An inside portion of the second flap 17 which is not joined to the first flap 16 is
 70 turned or folded upwardly and a portion 17a thus turned or folded up is then securely joined to itself at a front side area 19 and a rear side area 20 of the diaper. A folded portion of the second flap 17 located in a
 75 crotch area defined between said front side area 19 and said rear side area 20 is provided along its free end with elastic band 22 fixed thereon under its longitudinally stretched condition with adhesive (not shown) of hot melt type and enclosed by an envelope-like edge
 80 23 of the second flap 17. The first flap 16 is formed along its outer edge with a cut-away portion 24.

Such diaper is obtained, as seen in Figs. 7 to 9, by sandwiching the absorbent body 13 between the rectangular topsheet 11 and the rectangular backsheet 12, disposing a pair of narrow rectangular flap sheets 17 which have previously been provided with elastic
 85 bands 22 along laterally opposite sides of the topsheet 11 (see Fig. 6), joining these to said topsheet 11 with adhesive of hot melt type or any other suitable welding means (not shown) over areas indicated by two-dotted chain lines (oblique lines), then partially cutting away the sheets 11, 12 and 17, folding the
 90 inside portion of the sheet 17 back and finally fixedly joining the portion 17a thus folded back to itself in the front side area and the rear side area thereof also by use of adhesive of hot melt type or any other suitable
 95 welding means (not shown). As seen in Figs. 2 and 9, a transverse distance between the pair of said folded portions 17a is larger in the rear side area 20 than in the front side area 19 of the diaper. Thus, the rear side area 20 corresponding to the hip of the wearer and primarily exposed to excretions is wider than the front
 100 side area 19.

In the rear side area 20, the respective side flaps 14 are provided with tape fasteners 27 carrying thereon pressure sensitive adhesive and, upon actually wear-
 105 ing, the diaper is assembled, as seen in Fig. 1, by securing free ends of the respective fasteners onto the front side of the diaper.

The topsheet 11 may be of fibrous non-woven fabric, porous plastic film etc., and the backsheet 12 may be of plastic film, laminate sheet consisting of said plastic film and fibrous non-woven fabric etc. When said laminate sheet is employed, this is used with said non-woven fabric facing outwards. Although said plastic film is preferably air-permeable and
 110 waterproof, the air-permeability will be unnecessary if there is provided means to assist ventilation through the diaper between the inside and outside thereof. The absorbent body 13 may be, for example, of mat-like body consisting of fluff pulp mixed or not mixed with high-absorptivity polymer particles, covered at least on upper and lower sides with water-permeable sheets such as tissue paper and hydrophobic nets. In view of such material and configuration, it will be obviously understood that the absorbent body 13 is
 115 semi-rigid. The absorbent body 13 is securely joined to both the topsheet 11 and the backsheet 12 in a relatively stationary manner as with adhesive of hot melt type (not shown). The elastic bands 22 may be thread- or tape-like rubber, tape-like plastic foam or
 120 plastic film exhibiting an elasticity when heat-treated.

These materials used to manufacture the diaper are those commonly used for the disposable diaper and those skilled in the art will easily make a choice as desired.

5 The first flap 16 is, as has previously been mentioned, formed by the respective portions of the topsheet 11 and the backsheet 12 extending outwards from each of the laterally opposite edges of the absorbent body 13 and a portion of the second flap 17. 10 The second flap 17 is made of an air-permeable and waterproof sheet, preferably of fibrous non-woven fabric which has been subjected to waterproofing with silicone resin.

In an embodiment as shown by Figs. 8 and 9, lugs 28 laterally projecting from the front side area at opposite sides have their dimensions different from lugs 29 similarly projecting from the rear side area of the diaper, and the absorbent body 13 has lugs 30 only in the rear side area. However, the present invention is not limited to such configuration.

20 The side flaps 14 may be formed, as in an embodiment shown in Figs. 10 and 11, by folding back the outside portion(s) of both the wide topsheet 11 and the wide backsheet 12 or of only the backsheet 12. 25 However, when said separate sheet 17, different in nature from both the topsheet 11 and the backsheet 12, is used to form the side flaps 14, various advantages are obtained, which can not be expected when the side flaps 14 are formed by the extensions of the topsheet 11 and the backsheet 12. For example, 30 when the backsheet 12 is of air-permeable and waterproof material, the side flaps 14 may be formed by highly air-permeable and waterproof material to further reduce a stiffness possibly occurring inside the diaper. Furthermore, even if such highly air-permeable and waterproof material is of a relatively high cost, this leads to no economical disadvantage, because the side flaps 14, particularly the second flaps 17 may be narrow relative to the backsheet 12.

40 In an embodiment as shown by Fig. 12, each of the second flaps 17 is formed by sandwiching its longitudinal one side between the respective portions of the topsheet 11 and the backsheet 12 which together form the associated first flap 16, folding this back onto said portion of the topsheet 11 and joined thereonto, then 45 turning or folding a remaining or non-joined side outwards, joining the portion 17a thus turned or folded outwards onto itself along longitudinal opposite ends of this portion, and finally providing the non-joined folded portion with the associated elastic band 22. 50

Each of the second flaps 17 in an embodiment as shown by Fig. 13 is formed by joining its longitudinal one side onto the upper side of the associated first flap 16 at a position inside the side edge of the associated 55 first flap 16, turning or folding a remaining or non-joined side outwards, joining the portion 17a thus turned or folded outwards onto itself along longitudinal opposite ends of this portion, and finally providing a free end of the non-joined folded portion with the associated elastic band 22. 60

In an embodiment as shown by Fig. 14, each of the second flaps 17 is formed by laying it on the upper side of the associated first flap 16, joining it thereonto, 65 turning or folding a remaining or non-joined portion

outwards, joining the portion thus turned or folded outwards onto itself along longitudinal opposite ends of this portion and finally providing a non-joined central portion with the associated elastic band 22.

70 In an embodiment of Fig. 15, the second flap 17 is formed by bending the respective extensions of the topsheet 11 and the backsheet 12 upwardly in a -shape, inserting the associated elastic band 22 into a space defined inside a top of this bent portion and joining the inner surface of this portion together. 75

The second flap 17 in an embodiment as shown by Fig. 16 is formed by bending the extensions of the topsheet 11 upwards, joining one side of a sheet 31 onto the upper side of the backsheet 12 along an outer side portion of the extension thereof, joining the other side of said sheet 31 onto said bent portion of topsheet 11 in symmetrical relationship therewith and inserting the associated elastic band 22 into a space defined between the top ends of these bent portions. 80

85 As in the embodiment shown by Fig. 17, the second flap 17 is formed by joining lower ends of a sheet 32 bent in a -shape onto the extension of the topsheet 11 and inserting the associated elastic band 22 into a space defined inside the top of this bent portion.

90 The second flap 17 in the embodiment of Figs. 15 to 18 is preferably laid outwards and fixedly joined along longitudinal opposite ends thereof for the reason as will be mentioned. However, the present invention is not limited to such arrangement. In all the embodiments as shown, a portion 33 extending outwards from the second flap 17 in the crotch area has no contribution to provide seals around the thighs and therefore may be omitted except when this is necessary to form the pockets 18. 95

100 The diaper constructed in the manner as mentioned hereinabove in accordance with the present invention provides advantages as will be set forth below. When the pockets 18 are formed, excretions flowing towards the side flaps 14 are retained by these pockets and effectively prevented from leaking around the thighs. 105

The respective elastic bands 22 give the associated second flaps 17 effective elasticity and create the gathers. Contracting force of the elastic bands 22 act substantially upon overall of the associated second flaps 17, but such contracting force is reduced or suppressed on the lines 34 along which the respective second flaps 17 diverge from the associated first flaps 16, resulting in that a portion (major portion) of said contracting force is converted into an effect serving to turn the associated second flaps 17 up from the associated first flaps 16 along said lines 34 of divergence and thus the second flaps 17 are turned or folded up independently of the outer edges of the absorbent body 13. In the case in which the folding lines 35 of the respective folded portions 17a are distinctly formed independently of said lines 34 of divergence as seen in Figs. 4 and 6, the contracting force of the respective elastic bands 22 is reduced or suppressed also along these folding lines 35. With a consequence, even when the distance between each elastic band 22 and the associated outer edge of the absorbent body 13 is relatively small, the problems that the second flaps 17 under the contracting force of the associated elastic bands 22 might have their 110 115 120 125 130

contractibility and flexibility affected by the rigidity of the absorbent body 13 as well as the problems that the first flaps 16 and the absorbent body 13 might be subjected to unnatural stress-strain due to the contracting force of the respective elastic bands 22 are effectively solved. Accordingly, indecent appearance of the diaper as worn and discomfort for the wearer are avoided and a sufficient fitness of the diaper around the wearer's body, particularly an effective seal around the thighs are achieved, minimizing leakage of excretions.

The second flaps 17 have their free ends along which the elastic bands 22 are disposed directed outwardly and their longitudinal opposite ends being fixed against the elastic effect of the elastic bands 22 tending to lay down the second flaps 17 inwardly, the second flaps 17 are normally biased under a tension enough to maintain the second flaps 17 folded upwards and thereby prevented from being folded or turned inwardly when the diaper is worn. Moreover, movement of the wearer's thighs causes the second flaps 17 to be inclined or pivoted on said fixed longitudinal opposite ends and sail lines 34 of divergence so as to keep resilient contact with the wearer's skin without formation of a gap causing leakage of excretions around the thighs.

In view of the construction and the function as mentioned above, said lines 34 of divergence can be considered as rigidity gap lines or discontinuous rigidity lines which prevent the contracting force of the respective elastic band 22 from being transmitted beyond the second flap 17 to the first flap 16. To improve the contracting force of the elastic bands 22 and the contractibility of the second flaps 17, a height of each second flap 17 should be at least 10 mm, preferably 15 to 50 mm. Distance between the outer edge of the absorbent body 13 and said line 34 of divergence is not critical, but preferably less than 50 mm. The second flaps 17 may be close to the outer edges of the absorbent body 13 so far as the second flaps 17 have a desired height and said rigidity gap lines or discontinuous rigidity lines are formed.

Although not critical to solve the objects of the present invention, waist flaps 36 are formed by the respective portions of the topsheet 11 and the backsheets 12 extending outwards from the longitudinal opposite ends of the absorbent body 13, as seen in Figs. 2, 3, 5, 7 to 9, and 18. Second elastic bands 37 are disposed under longitudinal tension in a sandwich manner between the waist flaps 36, i.e., between the topsheet 11 and the backsheets 12. These elastic bands 37 are of plastic foam, particularly of polyurethane foam preferably having a thickness of 1 to 3 mm, a width of at least 5 mm and open cells of 20 to 70 kg/m³. The elastic bands 37 are joined, as shown in Fig. 18, on the topsheet 11 and the backsheets 12 with, for example, adhesive 38, 39 of hot melt type. Adhesive 38, 39 linearly extends transversely of the elastic bands 37 and applied onto the bands at regular intervals longitudinally of the bands or transversely of the diaper. Application interval of adhesive 38 used to join the topsheet 11 and the elastic bands 37 is larger than that for adhesive 39 used to join the backsheets 12 and the elastic bands 37. Thereby, the contractibility on an area on which the topsheet 11 is joined to the elastic

bands 37 is stronger than the contractibility on an area on which the backsheets 12 are joined to the elastic bands 37. In consequence, the waist flaps 36 appropriately follow curves of the wearer's body to achieve a good fitness. Said manner in which adhesive is applied so as to establish a difference of said contractibility may be so modified that said adhesive is applied in a stripe extending longitudinally of the elastic bands 37 while applied over a relatively wide area between the backsheets 12 and the elastic bands 37. In other words, the particular manner of application is not critical so long as said difference in the contractibility can be established. Furthermore, the elastic bands 37 preferably have their outer edges exposed between the respective outer edges of the topsheet 11 and the backsheets 12 so that a ventilation of the diaper between the inside and the outside thereof is facilitated through the elastic bands 37 made of plastic foam having open cells. To this end, it is required for this plastic foam to have said thickness and said cell density. Moreover, a distance between the longitudinal outer edge of the absorbent body 13 and the inner edge of the associated elastic band 37 is preferably at least 5 mm. With such distance, the fitness of the waist flaps 36 to the wearer's body, particularly the belly, is further improved.

CLAIMS

1. A disposable diaper comprising a water-permeable topsheet, a water-impermeable backsheets, a semi-rigid absorbent body interposed between said topsheet and backsheets, water-impermeable flexible side flaps extending laterally outwardly from opposite sides of said absorbent body, at least one elastic band extending longitudinally of each of said side flaps and adapted to form resilient gathers along each of said side flaps and fasteners disposed on opposite sides of one end of said diaper, wherein each of said side flaps comprises a first side flap and a second side flap, said first side flap extending laterally outwardly from said absorbent body and said second side flap extending from said first side flap in a laterally divergent manner and in that at least one of said elastic bands is associated with each of said second side flaps and acts thereon to cause at least an edge portion thereof to be held over at least a central portion of the length thereof in a substantially upstanding position relative to the first side flap from which it extends.

2. A disposable diaper including a water-permeable topsheet, a water-impermeable backsheets, a semi-rigid absorbent body interposed between said top and back sheets, water-impermeable side flaps having a high flexibility, disposed on laterally opposite sides of said absorbent body, elastic bands adapted to form elastic gathers extending longitudinally of said side flaps and tape fasteners disposed on laterally opposite sides in a rear side area of the diaper, wherein each of said side flaps includes a first flap disposed outside said absorbent body and a second flap diverged from said first side flap, having an associated one of said elastic bands incorporated therein and turned up under the elastic effect of said associated elastic band at least along a line of the divergence.

3. A disposable diaper as claimed in claim 1 or 2, wherein said second flap has its longitudinal one side

joined onto the upper side of said first flap, the other side directed outwards, of which longitudinally opposite ends fixed onto a front side area and a rear side area of the diaper and an intermediate portion rising upwards from a border line of the area over which said one side of the second flap is joined onto said first flap.

4. A disposable diaper as claimed in claim 1, 2 or 3, wherein said second flap has its longitudinal one side joined onto the upper side of said first flap and the other side folded back outwards of which longitudinally opposite ends are fixed onto the front side area and the rear side area of the diaper.

5. A disposable diaper as claimed in any of claims 1 to 4, wherein said second flap is made of a separate air-permeable and waterproof sheet different in nature from said first flap.

6. A disposable diaper as claimed in any of claims 1 to 4, wherein said first flap and said second flap are formed from the respective portions of said topsheet and said backsheet extending outwardly from each outer edge of said absorbent body.

7. A disposable diaper as claimed in any of the preceding claims, substantially as hereinbefore described with reference to and as illustrated in the accompanying drawings.